

Optional Accessories NSBon-xx

NSBon-42

THERMOELECTRIC ASSEMBLIES for harsh environments



- ✓ Sandstorm protection
- ✓ For harsh environments
- ✓ 24VDC | 220VAC Power supply
- ✓ Without exterior (external) fans

Thermoelectric Coolers or Thermoelectric Assemblies are designed to remove heat around critical components within an enclosure with IP66 protection category. These is a thermoelectric air conditioner using the Peltier effect. The main advantages of Thermoelectric Coolers over conventional compressor are:

- it can be controlled electronically;
- it is easily reversible when the current is reversed;
- it can work in harsh environments;

Thermoelectric Assembly NSBon-42 is fundamentally different from standard air-to-air coolers. Based on the calculations, a special design of ambient heat sink was created, which made it possible to remove exterior (external) fans.

External fans are the weakest link in any air-to-air cooler. They are constantly exposed to extreme ambient conditions and often fail for this reason, after that the cooling process of the internal heat sink stops.

The NSBon-42 design is 100% protected against sand, dust and water. Even a sandstorm will not disable the NSBon-42 cooler itself and equipment that it cools.

Technical Data

Operating voltage: 24 VDC; 220 VAC	Sand, dust and water protection is 100%
Cooling Capacity: 200 W	Without external fans outside
Operating Temp.: -40 to +70°C	Connection: Terminal
Dimensions: 500x214x208 mm	Fitting position: Variable
Weight: depends on the model	Protection category: IP66 / NEMA4



Ordering Information

NSBon-42	Thermoelectric Assembly. Series SandStorm_DC_200W, 24VDC, IP67. NSBox Cooling
----------	---