

Managed Industrial switch

> 8 PoE 30W | 60W | Passive

> 4 SFP/1G Uplink

> PoE ports: 4x 30W | 2x 60W | 2x Passive

The NSBox access Nodes are devised for the deployment of protected Outdoor Video Surveillance systems. The Nodes provide troubleproof operation of connected video cameras ranging from secure power supply, reliable data transmission, and protection of sensitive equipment from surges caused by lightning and grid power fluctuations. There is an ideal technological solution for time and money saving in any outdoor Video Surveillance projects for a large area ranging from highways, bridges, parking lots, airports, railways, sports facilities, hotels, parks, shopping malls, and construction sites.

The basic equipment of the NSBox-4044 includes: Wall mounting brackets, Mounting plate with DIN rails, terminal blocks, a two-pole circuit breaker, an electrical grounding bar, a fan with a thermostat, a set of cable glands. These modules can also be included in the assembly:

- Managed Industrial switch: uplink 4 SFP/1G, 8 TP/1G ports with PoE various power ;
- Power Supply 55VDC-360W or UPS NR-48VDC-360VA with mounting kit for batteries 7Ah x4;
- Climatic control system inside enclosure: thermostats, Fan Heater, Thermoelectric Cooler/ Assembly;
- Fiber Optic Distribution Frame (ODF) for connecting optical fibers with FC adapters, pigtails, patch cords;
- Lightning and surge protection for Ethernet PoE ports and power circuits 220VAC.

In order to include additional modules in assembling of Nodes needs to select Optional Accessories NSBon-xx.

NSBox-xxxxR with UPS are delivered without preset Batteries, only mounting kit for Batteries 7 | 15 | 45Ah is included.

The basic NSBox-4044 models are: NSBox-4044 | NSBox-4044H | NSBox-4044R | NSBox-4044HR

NSBox-4044 PX17F44F	Access Node: NSB-4040F3 enclosure with Fan, without Heater, with ODF; 55VDC-360W Power supply; WI-PMS312GF-I Switch: uplink 4 SFP/1G, 8 ports TP/1G PoE 802.3at/3bt/Passive; Reboot PD
NSBox-4044H PX17F44H	Access Node: NSB-4040H1F3 enclosure with Fan Heater; 55VDC-360W Power supply; WI-PMS312GF-I Switch: uplink 4 SFP/1G, 8 ports TP/1G PoE 802.3at/3bt/Passive for IP cameras; Reboot PDs
NSBox-4044R RX17F44F	Access Node: NSB-4040F3 enclosure with Fan, without Heater; UPS NR-48VDC-360VA with mounting kit for batteries 7Ah x4; WI-PMS312GF-I Switch: uplink 4 SFP/1G, 8 ports TP/1G PoE 802.3at/3bt/Passive; Reboot PD
NSBox-4044HR RX17F44H	Access Node: NSB-4040H1F3 enclosure with Fan Heater; UPS NR-48VDC-360VA with mounting kit for batteries 7Ah x4; WI-PMS312GF-I Switch: uplink 4 SFP/1G, 8 ports TP/1G PoE 802.3at/3bt/Passive; Reboot PD

Technical Data



Input Voltage Power consumption	: 100 - 240VAC 500 W (no more)
Enclosure material (cabinet, door)	: Sheet steel, powder-coated, primed
Protection category IP/NEMA IK Code	: IP66 / NEMA4 IK08
Enclosure mounts	: Wall or pole mount with NSBon-01 kit
Operating temp. with thermal insulation	: -40°C to +60°C -50°C to +60°C
Dimensions (no cable glands)	: 400 x 400 x 230 mm
Shipping weight (approx.)	: 12 kg 22 kg for R models (with batteries)
Fiber Optic Distribution Frame (ODF)	: mounted with 4 FC adapters, pigtails, patch cords
Heater with thermostats (for H models)	: NSBon-18 option, Fan Heater
Uninterruptible Power Supply (for R models)	: NR-48VDC-360VA with mounting kit for batteries 7Ah x4

Hardware specification	Managed Industrial switch WI-PMS312GF-I
8x 10/100/1000T RJ45 with PoE various power	IEEE 802.3at / 802.3bt (PD Alive Check) / Passive PoE
4x 100/1000M SFP slots (with DDM)	Total PoE Budget 300W, PSE 30W/port, max 60W

Management Interface | Diagnostic

Console/CLI, Web GUI, Telnet, SNMP, Syslog, RMON

Network Protocols :

Ring Topology: ERPS, EAPS; Spanning Tree: STP, RSTP, MSTP; VLAN: Port-based, 802.1q tag-based; IGMP v1/v2/v3 & MLDv1/2 Snooping; QoS: 802.1p, 8 queues per port, WRR/SP/WFQ; DHCP Snooping; Multicast/Broadcast/Unicast Storm Control; Security: RADIUS, TACACS+, SSH, AAA, ACL; STNP; Static Routing.

