

NSBox comparison table

How many PoE video cameras can be connected to NSBox				Added option	Dimensions of the cabinet	Power supply / UPS	Pmax. on PoE ports	Total PoE Budget	Uplink
2-4 PoE	4 PoE	8 PoE	16 PoE						
NSBox with Unmanaged PoE Switches									
NSBox-123					300x300x210	48VDC-100W	30 W	120 W	1 TP/1G
NSBox-123L				4G LTE	300x300x210	48VDC-100W			4G LTE
NSBox-124R				UPS	380x380x210	UPS 24VDC-240VA 2x 15Ah	30 W	120 W	1 TP/1G
NSBox-124S-30				SUN	380x380x210	UPS 24VDC-240VA 2x 15Ah			1 TP SUN
NSBox-124SL-30				SUN LTE	380x380x210	UPS 24VDC-240VA 2x 15Ah			SUN LTE
NSBox-p124S-30				SUN GRP	400x400x200	UPS 24VDC-240VA 2x 15Ah	30 W	120 W	1 TP SUN
	NSBox-242				300x400x210	48VDC-150W	30 W	120 W	2 Gigabit SFP
	NSBox-242H			Heater	300x400x210	48VDC-150W			
	NSBox-242R			UPS	380x380x210	UPS 48VDC-155VA 4x 7Ah	30 W	120 W	2 Gigabit SFP
	NSBox-p242			GRP	300x400x200	48VDC-150W			
	NSBox-p242R			UPS GRP	400x400x200	UPS 48VDC-155VA 4x 7Ah			
	NSBox-442				380x380x210	55VDC-360W	60 W 95 W	240 W	4 Gigabit 2 SFP + 2 TP
	NSBox-442R			UPS	380x380x210	UPS 48VDC-360VA 4x 7Ah			
		NSBox-282			300x400x210	48VDC-240W	30 W	240 W	2 Gigabit SFP/TP Combo
		NSBox-282H		Heater	300x400x210	48VDC-240W			
		NSBox-282R		UPS	380x380x210	UPS 48VDC-240VA 4x 7Ah			
NSBox with Managed PoE Switches L2/ L2+									
	NSBox-2040				300x400x210	48VDC-150W	36 W	144 W	2 Gigabit SFP
	NSBox-2040R			UPS	380x380x210	UPS 48VDC-155VA 4x 2.2Ah			
	NSBox-p2040			GRP	300x400x200	48VDC-150W	36 W	144 W	2 Gigabit SFP
	NSBox-p2040R			UPS GRP	400x400x200	UPS 48VDC-155VA 4x 2.2Ah			
	NSBox-2041				300x400x210	55VDC-360W	95 W 802.3bt	240 W	3 Gigabit 2 SFP + 1 TP
	NSBox-2041R			UPS	380x380x210	UPS 48VDC-360VA 4x 7Ah			
		NSBox-4044			400x400x230	55VDC-360W	30 W	300 W	4 Gigabit SFP
		NSBox-4044R		UPS	400x400x230	UPS 48VDC-360VA 4x 7Ah			
		NSBox-p4044H		GRP	400x600x230	55VDC-360W	30 W	300 W	4 Gigabit SFP
		NSBox-p4044HR		UPS GRP	400x600x230	UPS 48VDC-360VA 4x 7Ah			
		NSBox-4080			380x380x210	48VDC-360W	30 W	240 W	4 Gigabit SFP
		NSBox-4080R		UPS	380x380x210	UPS 48VDC-360VA 4x 7Ah			
		NSBox-4082			380x380x210	55VDC-360W	60 W	240 W	4 Gigabit 2 SFP + 2 TP
		NSBox-4082R		UPS	380x380x210	UPS 48VDC-360VA 4x 7Ah			
			NSBox-4161		380x600x210	55VDC-500W	30 W	320 W	4 Gigabit 2 SFP + 2 TP
			NSBox-4161R	UPS	380x600x210	UPS 48VDC-500VA 4x 7Ah			
* Additional features:									
BASIC: DIN Rails; Cable glands; Circuit breaker; Terminal blocks					IP66 protection; ODF with adapters: FIBER*				
HEATING: Fan Heater 75W 220 or 115VAC; Thermostats NC/NO					Operating Temp.: -40 to +60°C, -50 to +60°C with IZOLUX*				
FIBER: ODF with 4/8 FC adapters, pigtails, patch cords					Surge protection for power circuits 110-220VAC: NSBon-09/10/11				
IZOLUX: Thermal insulation of foamed polyethylene					Surge protection for Ethernet ports: NSBon-14/15				
NSBox-xxxxC E H L N R		R - installed UPS L - installed 4G LTE Router H - installed Heater N - installed NVR C - installed Thermoelectric Cooler E - explosion proof enclosure							